

**PATENT**

"Express Mail" mailing label number  
EL 756 224 048 US

Date of Deposit  
July 5, 2001

**Attorney Case No. 659-867**  
**Client Case No. 17,022**

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTORS:

Cindy L. Price	Appleton, WI
Suzanne A. Schmoker	Oshkosh, WI
Lori S. Schutkoske	Butte des Morts, WI
Jesse P. Sorenson	Little Chute, WI
Paul T. VanGompel	Hortonville, WI
Jerome S. Veith	Menasha, WI

TITLE:

REFASTENABLE ABSORBENT GARMENT

ATTORNEY:

Andrew D. Stover  
Reg. No. 38,629  
BRINKS HOFER GILSON &  
LIONE LTD.  
P.O. Box 10395  
Chicago, Illinois 60610  
(312) 321-4200

## REFASTENABLE ABSORBENT GARMENT

### BACKGROUND

5           The present invention relates generally to a refastenable absorbent garment, and in particular, to a refastenable absorbent garment having a hook-type mechanical fastener that engages a landing member.

10           Absorbent garments can be configured in many different forms. For example, absorbent garments can be configured as a pant-type, pull-on garment, or as a diaper-type product that is drawn up between the legs and fastened about the waist with various fastening systems. Often, in the latter configuration, the fastening systems are configured to allow the user to detach and reattach various fasteners so as to provide a refastenable absorbent garment. For example, some fastening systems include one or more tabs that are secured to a back portion of the garment and which releasably engage a front portion of the garment.

15           Often, the tabs are provided with a mechanical hook system that engages a landing portion configured with loop-type material. Conventional loop-type materials can be relatively expensive to manufacture, however. In addition, the loop-type material is typically formed as a separate patch of material, which is attached to an underlying backsheet or body panel. The additional material, and the step of incorporating the patch into the garment, can add to the overall cost of the product.

20           In other garments, the landing portion may include an elastic member or elastomeric material, which can shrink portions of the landing portion material and thereby make it more susceptible to entanglement with the hook-type fasteners. Such aspects can increase the bulk of the garment beneath the clothes of the user, and can incur further expense in the manufacture thereof by virtue of the requirement for the additional elastic material.

## SUMMARY

Briefly stated, in one aspect, the invention is directed to an absorbent garment comprising a body panel comprising a non-woven material. In one embodiment, the non-woven material is a spunbond material having a pattern of discrete bonded areas. The body panel has a non-elasticized area. A hook-type fastener member comprises a high-density array of hooks with a hook density of at least 60 hooks per square centimeter. At least a portion of the array of hooks is engaged with the non-woven material at the non-elasticized area of the body panel.

10 In one preferred embodiment of the invention, between about 5% and 25% of the non-woven material comprises the bonded area. In another preferred embodiment, the non-woven material has a basis weight of between about .3 osy and about 2.0 osy.

In another aspect of the invention, an absorbent garment comprises a front body panel comprising opposite side edges and a rear body panel comprising opposite side edges, wherein the opposite side edges of the front and rear body panels are joined to form a side seam. A hook-type fastener member comprises a carrier member secured to the front body panel in front of the side seam and a plurality of hooks, wherein at least a portion of the plurality of the hooks are engaged with the front body panel.

20 In one preferred embodiment, the front body panel comprises a pair of side portions defining the opposite side edges which are mounted to the opposite side edges of the rear body panel. A landing member extends between the side portions, wherein the hooks are engaged with the landing member. In a preferred embodiment, the side portions are initially breakably attached to opposite sides of the landing member along respective lines of weaknesses.

In one preferred embodiment, the entire thickness of one or more of the body panels is a non-woven material. In another preferred embodiment, the entire outer, garment side surface of the body panel is made of the same non-woven material. In one embodiment, the one or more body panels are made of

two or more substrates or layers or of a non-woven material that are bonded one to the other. In one preferred embodiment, elastic members are disposed between the bonded substrates or layers. In alternative embodiments, the elastic members can be secured on top or below the material, along one or more  
5 surfaces.

In yet another aspect of the invention, an absorbent garment comprises a body panel having a length and a fastening member comprising at least two engagement portions releasably engaging the body panel. Each of the engagement portions having an engagement length, wherein the sum of the  
10 engagement lengths is at least about 20% of the body panel length.

In another aspect, the body panel comprises a front body panel. A rear body panel, having a length, is secured to the front body panel along a seam, which has a length. The fastening member comprises a carrier member having a length. In one preferred embodiment, the length of the carrier member is at  
15 least about 50% of the length of the seam. In another preferred embodiment, the length of the carrier member is at least about 50% of the length of the rear body panel.

In another aspect of the invention, a method of securing an absorbent garment to a user is provided. In yet another aspect, a method of  
20 manufacturing an absorbent garment is provided.

The present invention provides significant advantages over other absorbent garments and methods for the use and manufacture thereof. For example, the body panel can be made out of a relatively low basis weight non-woven material, which provides a landing area for the hook-type fasteners  
25 without the need for an additional loop-type material. In this way, the absorbent garment can be made with less expense. For example, in one embodiment, the body panel is made of one or more substrates of non-woven material, which is relatively inexpensive to manufacture yet provides a soft and flexible surface that contacts the user's body. In addition, portions of the body  
30 panel can be made without elastic members so as to provide a better fit for the

user that has a less bulky appearance, and which reduces the overall expense of the garment. In addition, by making the absorbent garment refastenable, it can be applied without needing to pull it on or off like a pant-like garment. In addition, the garment can be made bigger or smaller simply by adjusting the positioning of the fasteners.

Moreover, in one particular application, wherein the garment is used by adults, for example with occasional incontinence problems, the fastening system may be disengaged and engaged repeatedly by the user while the garment remains unsoiled over an extended period of time. At the same time, the garment can initially be pulled on like a pant-like garment before the lines of weaknesses are broken. The non-woven materials disclosed and described herein do not tend to become stringy and the fibers do not tend to pull away from the garment, as is experienced with some loop materials. As such, the material provides a landing area that is particularly suited for repeated engagements with the hook-type fastening members, and in particular, high-density hook-type fasteners.

In addition, the fastener member, with its at least two engagement portions releasably engaging the body panel, allows the user to independently control both the waist region and the leg region of the front body panel, while also providing the user with a pant-like fit. At the same time, the user can adjust one or the other of the engagement portions without the garment coming undone. The total length of the engagement portions controls a larger area of the body panel. At the same time the length of the carrier member provides the user with control of the body panel.

The present invention, together with further objects and advantages, will be best understood by reference to the following detailed description taken in conjunction with the accompanying drawings.

## BRIEF DESCRIPTION OF THE DRAWINGS

Many of the features and dimensions portrayed in the drawings, and in particular the presentation of layer thicknesses and the like, have been  
5 somewhat exaggerated for the sake of illustration and clarity.

FIGURE 1 is a front view of one embodiment of an absorbent garment in a fastened configuration.

FIGURE 2 is a bodyside plan view of one embodiment of an absorbent garment in an unfastened flat configuration.

10 FIGURE 3 is a bodyside plan view of another embodiment of an absorbent garment in an unfastened flat configuration.

FIGURE 4 is an exploded cross-sectional view of the absorbent garment taken along line 4-4 in Figure 3.

15 FIGURE 5 is an exploded cross-sectional view of the absorbent garment taken along line 5-5 in Figure 3.

FIGURE 6 is an exploded cross-sectional view of the absorbent garment taken along line 6-6 in Figure 3.

FIGURE 7 is an enlarged plan view of the front body panel material.

20 FIGURE 8 is an enlarged side cross-sectional view of a hook-type fastener engaging the front body panel material.

FIGURE 9 is partial side view of one preferred embodiment of an absorbent garment fastening system.

FIGURE 10 is partial side view of an alternative preferred embodiment of an absorbent garment fastening system.

25 FIGURE 11 is partial side view of an alternative preferred embodiment of an absorbent garment fastening system.

FIGURE 12 is a two-dimensional rendition of a surface of a non-woven spunbond material.

30 FIGURE 13 is a three-dimensional rendition of the surface of the non-woven spunbond material shown in FIG. 12.

FIGURE 14 is a two-dimensional rendition of a surface of a non-woven point unbonded material.

FIGURE 15 is a three-dimensional rendition of the surface of the non-woven point unbonded material shown in FIG. 14.

5        FIGURE 16 is a BSE/HICON photomontage of a non-woven spunbond material at 20X magnification.

FIGURE 17 is a BSE/HICON photomontage of a non-woven point unbonded material.

## 10        **DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EMBODIMENTS**

It should be understood that the term "longitudinal," as used herein, means of or relating to length or the lengthwise direction, and in particular, the direction running between the front and back of the user. The term "laterally,"  
15 as used herein means situated on, directed toward or running from side to side, and in particular, a direction running from the left to the right of a user, and vice versa. The terms "upper," "lower," "inner," and "outer" as used herein are intended to indicate the direction relative to the user wearing an absorbent garment over the crotch region, while the terms "inboard" and "outboard" refer  
20 to the directions relative to a centerline 8 of the garment. For example, the terms "inner" and "upper" refer to a "bodyside," which means the side closest to the body of the user, while the terms "outer" and "lower" refer to a "garment side."

The term "bodyside" should not be interpreted to mean in contact with  
25 the body of the user, but rather simply means the side that would face toward the body of the user, regardless of whether the absorbent garment is actually being worn by the user and regardless of whether there are or may be intervening layers between the component and the body of the user. Likewise, the term "garment side" should not be interpreted to mean in contact with the  
30 garments of the user, but rather simply means the side that faces away from the body of the user, and therefore toward any outer garments that may be worn by

the user, regardless of whether the absorbent garment is actually being worn by a user, regardless of whether any such outer garments are actually worn and regardless of whether there may be intervening layers between the component and any outer garment.

5 Referring to FIGS. 1-6, an absorbent garment **2** includes a first, front body panel **4** and a second, rear body panel **6**. The first and second body panels each have an inner, bodyside surface **10** and an outer, garment side surface. The first, front body panel **4** has a length (FPL), which is measured between opposed first and second terminal edges **16** and **20**, as shown in FIGS. 10 9-11, and which is less than the overall length of the absorbent garment. Likewise, the second, rear body panel **6** has an overall length (RPOL), which is measured between opposed first and second terminal edges **14** and **18**, as shown in FIGS. 2 and 3, and which is also less than the overall length of the absorbent garment. Each of the first and second body panels has an outboard edge **24**, **28** 15 formed along the outer periphery of laterally opposed side portions of the first and second body panel. The outboard edge of the second body panel **6** has a length (RPL), which is preferably the same length (FPL) of the front body panel. It should be understood that the outboard edges of the front and rear body panels can be different lengths.

20 As shown in FIGS. 2 and 3, the second body panel also includes opposite tapered edges **26**. The first terminal edges **14**, **16** of the first and second body panels are longitudinally spaced to form an opening **34** therebetween in the crotch region of the garment, while the second terminal edges **20**, **18** of the first and second body panels form front and back waist 25 edges respectively.

Referring to FIGS. 1-6, one or more, and preferably a plurality, meaning two or more, laterally extending elastic elements **36** are secured to each of the first and second body panels along the terminal edges **20**, **18**. Preferably, a plurality of laterally extending elastic elements are longitudinally 30 spaced across substantially the entire length of the waist portion of the rear



body panel **6**, although they may be spaced across a lesser length. In various preferred embodiments, at least one, and preferably between about 16 and 21 laterally extending elastic elements are longitudinally spaced along the length of the body panel. For example, in one embodiment, the elastic elements are

5 spaced about 0.25 inches from each other. It should be understood, that in an alternative embodiment, one or more separate waist bands, with or without elastic elements, can be secured to one or both of the rear and front body panels, preferably along the upper terminal edges thereof.

The front body panel preferably has a “non-elasticized” area **17** wherein

10 there are no laterally extending elastic elements, or other elastic or elastomeric backing members, incorporated therein or making up any portion of the thickness or cross-section of the body panel at that area, such that the material is or can be gathered. Preferably, one or more elastic elements **36** extend laterally along the outer terminal edge **20** and are longitudinally spaced along

15 about a one-inch wide portion of the front body panel. In this embodiment, the non-elasticized area **17** is formed between the elastic elements **36** extending along the upper waist portion and elastic elements **38** extending along the lower terminal edge defining the leg opening. In various embodiments, at least one, and preferably from about 4 to about 11 elastic elements are spaced along the

20 upper waist portion of the front body panel. One or more leg elastic elements **38** can be secured along the inner terminal edges of the body panels **4**, **6** and an absorbent composite **50** to form a gasket with the leg of the user.

In addition, the term “non-elasticized” should further be understood as also meaning non-gathered, wherein the material does not have any pillows,

25 ripples or other substantially three-dimensional undulations or aspects associated therewith, regardless of whether such gathered material is formed by incorporating various elastic elements, or by bonding various non-elastic layers, one or more of which may be stretched, to other layers having a different surface area, as disclosed for example in U.S. Patent No. 5,763,041, which is

hereby incorporated herein by reference. Rather, the material lies substantially flat in the non-elasticized area.

The various waist and leg elastic elements can be formed from rubber or other elastomeric materials. One suitable material is a LYCRA® elastic material. For example, the various elastic elements can be formed of LYCRA®  
 5 XA Spandex 540, 740 or 940 detex T-127 or T-128 elastics available from E.I. duPont De Nemours and Company, having an office in Wilmington, Delaware.

As shown in FIGS. 4-6, each body panel is preferably formed as a composite, or laminate material comprising two non-woven layers 40,  
 10 otherwise referred to as substrates or laminates, with the plurality of elastic strands 38, 36 sandwiched therebetween. The elastic strands 36, 38 are positioned in the waist regions and along the leg perimeters as explained above. The two layers 40 are then bonded with various adhesives 41, such as hot melt, or by other techniques, including for example and without limitation ultrasonic  
 15 bonding and heat pressure sealing. In this way, the body panels are preferably made of a relatively homogenous non-woven material, whether made of one or more layers or substrates, and preferably without any additional film materials or other types of materials being laminated thereto. As such, the body panels can be made with a relatively low basis weight, yet still exhibit requisite  
 20 strength properties while remaining relatively soft to the touch. It should be understood that the body panels can be made of a single layer or substrate of non-woven material, or can be comprised of more than two layers or substrates.

At the same time, it should be understood that at least the outermost substrate, layer or web of the body panel is preferably constructed of the non-  
 25 woven materials described herein. The non-woven material preferably makes up and defines the entire outer, garment-side surface of the body panel, and is preferably a relatively homogenous material over the entire extent of the body-panel, without the addition of any additional landing materials secured thereto. Of course, it should be understood that other knitted or woven fabrics, non-  
 30 woven fabrics, polymer films, laminates and the like can be secured, by

bonding or other lamination techniques, to the bodyside surface of the outermost non-woven material substrate. The term "non-woven" web or material, as used herein, means a web having a structure of individual fibers or filaments that are interlaid, but not in an identifiable manner and without the aid of textile weaving or knitting, as in a knitted or woven fabric.

The non-woven layers or substrates **40** are preferably made by spunbonding. Spunbond nonwoven webs or materials are made from melt-spun filaments or spunbonded fibers **25**, shown in FIGS. 7 and 8, which refers to small diameter fibers that are formed by extruding molten thermoplastic material as filaments from a plurality of fine, usually circular capillaries of a spinneret with the diameter of the extruded filaments then being rapidly reduced, for example, by non-eductive or eductive fluid-drawing or other well known spunbonding mechanisms. The production of spunbound nonwoven webs is described in U.S. Patent No. 4,340,563 to Appel et al., U.S. Patent No. 3,692,618 to Dorschner et al., U.S. Patent No. 3,802,817 to Matsuki et al, U.S. Patent No. 3,502,763 to Hartmann, U.S. Patent No. 3,276,944 to Levy, U.S. patent No. 3,502,538 to Peterson, and U.S. patent No. 3,542,615 to Dodo et al, all of which are incorporated herein by reference. The melt-spun filaments formed by the sponbond process are generally continuous and have diameters larger than 7 microns, more particularly, between about 10 and 30 microns. Another frequently used expression of fiber or filament diameter is denier, which is defined as grams per 9000 meters of a fiber or filament. The fibers may also have shapes such as those described in U.S. Patent No. 5,277,976 to Hogle, et al, U.S. Patent No. 5,466,410 to Hills and U.S. Patent Nos. 5,069,970 and 5,057,368 to Largman et al., all of which are incorporated herein by reference. The spunbond filaments usually are deposited, by one or more banks, onto a moving foraminous belt or forming wire where they form a web. Spunbonded filaments generally are not tacky when they are deposited onto the collecting surface.

Spunbond fabrics typically are stabilized or consolidated (pre-bonded) in some manner immediately as they are produced in order to give the web sufficient integrity to withstand the rigors of further processing into a finished product. This stabilization (prebonding) step may be accomplished through the use of an adhesive applied to the filaments as a liquid or powder which may be heat activated, or more commonly, by compaction rolls. As used herein, the term "compaction rolls" means a set of rollers above and below the web used to compact the web as a way of treating a just produced, melt-spun filament, particularly spunbond, web, in order to give the web sufficient integrity for further processing, but not the relatively strong bonding of secondary bonding processes, such as through-air bonding, thermal bonding, ultrasonic bonding and the like. Compaction rolls slightly squeeze the web in order to increase its self-adherence and thereby its integrity.

An alternative means for performing the pre-bonding step employs a hot air knife, as described in U.S. Patent application Ser. No. 362,328, filed Dec. 22, 1994, which is incorporated herein by reference. Briefly, the term "hot air knife" means a process of pre-bonding a just produced melt-spun filament, particularly spunbond, web, in order to impart the web with sufficient integrity, i.e., increase the stiffness of the web, for further processing. A hot air knife is a device that focuses a stream of heated air at a very high flow rate, generally from about 300 to about 3000 meters per minute (mi/min.), or more particularly from about 900 to about 1500 m/min., directed at the nonwoven web immediately after its formation. The air temperature usually is in the range of the melting point of at least one of the polymers used in the web, generally between about 90° C. and about 290° C. for the thermoplastic polymers commonly used in spunbonding. The control of air temperature, velocity, pressure, volume and other factors helps avoid damage to the web while increasing its integrity.

The hot air knife's focused stream of air is arranged and directed by at least one slot of about 3 to about 25 millimeters (mm) in width, particularly

about 9.4 mm, serving as the exit for the heated air towards the web, with the slot running in a substantially cross-machine direction over substantially the entire width of the web. In other embodiments, there may be a plurality of slots arranged next to each other or separated by a slight gap. The at least one slot usually, but not necessarily, is continuous, and may be comprised of, for example, closely spaced holes. The hot air knife has a plenum to distribute and contain the heated air prior to its exiting the slot. The plenum pressure of the hot air knife usually is between about 2 to about 22 mmHg, and the hot air knife is positioned between about 6.35 mm and about 254 mm, and more particularly from about 19.05 to about 76.20 mm above the forming surface. In a particular embodiment, the hot air knife plenum's cross-sectional area for cross-directional flow (i.e., the plenum cross-sectional area in the machine direction) is at least twice the total slot exit area. Since the foraminous wire onto which spunbond polymer is formed generally moves at a high rate of speed, the time of exposure of any particular part of the web to the air discharge from the hot air knife typically is less than a tenth of a second and generally about one hundredth of a second, in contrast with the through-air bonding process, which has a much longer dwell time. The hot air knife process has a great range of variability and control over many factors, including air temperature, velocity, pressure, and volume, slot or hole arrangement, density and size, and the distance separating the hot air knife plenum and the web.

The spunbond process also can be used to form bicomponent spunbond nonwoven webs as, for example, from side-by-side (or sheath/core) linear low density polyethylene/polypropylene spunbond bicomponent filaments. A suitable process for forming such bicomponent spunbond nonwoven webs is described in U.S. Pat. No. 5,418,045 to Pike et al., which is incorporated herein by reference in its entirety.

Commercially available thermoplastic polymeric materials can be advantageously employed in making the fibers or filaments from which pattern-unbonded nonwoven material 4 is formed. As used herein, the term "polymer"

shall include, but is not limited to, homopolymers, copolymers, such as, for example, block, graft, random and alternating copolymers, terpolymers, etc., and blends and modifications thereof. Moreover, unless otherwise specially limited, the term "polymer" shall include all possible geometrical configurations of the material, including, without limitation, isotactic, syndiotactic and random symmetries. As used herein, the terms "thermoplastic polymer" or "thermoplastic polymeric material" refer to a long-chain polymer that softens when exposed to heat and returns to its original state when cooled to ambient temperature. Preferably, the spunbond fibers are made of a polypropylene.

Other alternative thermoplastic materials include, without limitation, poly(vinyl chloride)s, polyesters, polyamides, polyfluorocarbons, polyolefins, polyurethanes, polystyrenes, polyethylenes, poly(vinyl alcohol)s, caprolactams, and copolymers of the foregoing. The fibers or filaments used in making the nonwoven material may have any suitable morphology and may include hollow or solid, straight or crimped, single component, bicomponent or multicomponent, biconstituent or multiconstituent fibers or filaments, and blends or mixes of such fibers and/or filaments, as are well known in the art.

After the nonwoven web is formed, the pre-bonded or unbonded web is passed through a suitable process or apparatus, including for example a calendar roll, to form a pattern of discrete bonded areas. The term "discrete" as used herein means individual or disconnected, and is contrasted with the term "continuous" as used in U.S. Patent No. 5,858,515 to Stokes et al, which describes pattern-unbonded, or point un-bonded (PUB), nonwoven fabrics having continuous bonded areas defining a plurality of discrete unbonded areas.

In one embodiment, the calendar stack (not shown) includes an anvil roll and a pattern roll, which is heated and includes various raised landing portions. The raised portions of the pattern roll thermally bond the fibers to form the bonded areas **23**, as shown for example in FIG. 7. The bonds can made of any shape and size. Preferably, the percent bonded area of the web is between about 5% and 25% of the area of the web, and is more preferably between about 10% and

15%. Thereafter, the bonded substrate can be bonded to another substrate with the elastic members disposed therebetween.

In the various configurations of the invention, the basis weight of each of the body panel non-woven spunbond material substrates is preferably about 0.6 osy. In other preferred embodiments, the basis weight of each substrate can be between at least about 0.3 and about 2.0 osy, and preferably between about 0.5 osy and about 1.5 osy, and more preferably between about 0.5 osy and about 1.0 osy. Even with a relatively low percent area bonding, the relatively low basis weight non-woven spunbond material exhibits strength and tear characteristics allowing it to be used as a body panel. Other materials that may be used as the non-woven material include various meltblown materials, and also bonded-carded materials.

The body panels 4, 6 non-woven material is preferably substantially hydrophobic, which may optionally be treated with a surfactant or otherwise process to impart a desired level of wettability and hydrophilicity. In one particular embodiment of the invention, the body panel is a nonwoven, wire-weave spunbond polypropylene fabric composed of about 1.6 denier fibers formed into a web having a basis weight of about 0.6 osy. One suitable non-woven material is the Corinth 0.60 osy, 1.6dpf wireweave, nonwetable Metalocene (EXXON ACHIEVE 2854 PP) Spunbond material manufactured by Kimberly-Clark Corporation, the assignee of the present application.

The preferred non-woven materials, which are relatively smooth can be distinguished from other non-woven materials that have been used as loop materials by a comparison of various properties. For example, and referring to FIGS. 12-15, Scanning White-Light Interference Microscopy (SWLIM) tests were performed on two materials, a 0.60 osy wire-weave spunbond laminate material and a 2.0 osy point-unbonded (PUB) material to determine various roughness parameters. The 2D and 3D representations of FIGS. 12-15 are each a 3 x 3 field montage, having a size of about 6.7 mm x 5.1 mm. The results of the SWLIM tests are referenced in Table 1.

Table 1: SWLIM Tests

	<b>Ra</b>	<b>Rku*</b>	<b>RP</b>	<b>RPm</b>	<b>Rq</b>	<b>Rsk*</b>	<b>Rt</b>	<b>Rv</b>	<b>Rvm</b>	<b>Rz</b>
2.0 osy	232388.8	2.03	920876.1	880239.5	261447.7	0.61	1399770	-478894.1	-478459.2	1358699
PUB										
0.6 osy	59685.93	5.15	301757.1	280871.7	81723.13	-0.73	725239.3	-423482.3	-413034.9	693906.6
spun-										
bond										

\*Rku, Rsk – no units  
All other measurements are in nanometers

As used in Table 1, **Ra** is the “roughness average,” which is defined as the mean height of the surface calculated over the entire array. Effects of single spurious peaks are averaged out. **Ra** may average out detail needed to quantify a complex surface. **Rq** is the “root mean square roughness” (rms), which is defined as the rms average of the measured height deviations taken within the evaluation area and measured from the mean linear surface. **Rq** is used to calculated skewness and kurtosis. If a surface has a profile that contains no large deviations from the mean surface level, the values of **Ra** and **Rq** will be similar. If there are appreciable numbers of large bumps or holes, the largest values of the profile height function will dominate the surface statistics and **Rq** will be larger than **Ra**. **Rt** is the “maximum height of the profile,” which is defined as the vertical distance between the highest and the lowest points on the evaluation area. **Rz** is the “average maximum height of the profile,” which is defined as the average of the greatest peak-to-valley separations. **Rpm** is the “average maximum profile peak height,” which is defined as the mean peak height of the entire dataset. **Rpm** characterizes surface based on peaks in the surface profile. **Rvm** is the “average maximum profile valley depth,” which is defined as the mean peak valley for the entire data set. **Rsk** is the “skewness,” which is defined as a measure of the asymmetry of the profile. The sign of the skewness will tell whether the farther points are proportionately above (positive



skewness) or below (negative skewness) the mean surface level. **Rku** is the “kurtosis,” which is defined as the measure of the peakedness of the profile. A random surface will have a kurtosis value close to 3. The farther the kurtosis value is from 3, the less random (the more repetitive) the surface is. A smooth surface with few high and low extreme points will have a value less than 3. **Rv** is the “maximum profile valley depth,” which is defined as the maximum depth of the profile below the mean line for the entire data set. **Rp** is the “maximum profile peak height,” which is the maximum height of the profile above the mean line for the entire data set.

As can be seen from Table 1, and FIGS. 12 and 13, the preferred non-woven spunbond material has a considerably lower roughness average (Ra) and root mean square roughness (Rq) than the PUB material. At the same time, the non-woven spunbond material can be engaged by high-density hook materials, described herein below, to provide adequate shear and peel strength, so as to maintain the garments on the user during normal wearing conditions. In various preferred embodiments, Ra is less than about 200  $\mu\text{m}$ , preferably less than about 150  $\mu\text{m}$ , and more preferably less than about 100  $\mu\text{m}$ , and even more preferably less than about 70  $\mu\text{m}$ . Also in various preferred embodiments, Rq is less than about 250  $\mu\text{m}$ , preferably less than about 200  $\mu\text{m}$ , and more preferably less than about 150  $\mu\text{m}$ , and even more preferably less than about 100  $\mu\text{m}$ .

In another test, described as a back-scatter electron detection and TY 51 Hicontrast Polaroid® film (BSE/HICON) Surface Porosity test, 6 samples (1/2"x3/4") of the spunbond and pub materials were taken from a 4"x6" section of material. The 6 samples were gold coated with a sputter coater. Using back-scatter electron detection, photomontages, shown in FIGS. 16 and 17, were prepared for each material at 20X magnification. The photomontages were analyzed, and data was obtained, using the QUANTIMET 970 Image Analysis System, available from Leica Corp., located in Deerfield, Illinois. In

particular, the QUIPS CONWID routine, set forth at Appendix 1, was used for performing this work. The results of those tests are reported at Tables 2-9.

Table 2: DISTRIBUTION OF COUNT vs PERCAREA

5

Cambridge Instruments QUANTIMET 970 QUIPS/MX: V08.00 USER:

ROUTINE : CONWID

SPECIMEN : .6 OSY WW SB LAMINAT

10      Total PERCAREA    =    972.    Mean = 40.5 Std Dev = 3.65  
      Undersize Count    +    0    Oversize Count =    0.

PERCAREA (% AREA)

         LIMITS                      COUNT

PERCAREA (%)

AREA)

LIMITS

COUNT

0. - 6.00	0.	:
6.00 - 12.00	0.	:
12.00 - 18.00	0.	:
18.00 - 24.00	0.	:
24.00 - 30.00	0.	:
30.00 - 36.00	2.	:****
36.00 - 42.00	14.	:*****
42.00 - 48.00	8.	:*****
48.00 - 54.00	0.	:
54.00 - 60.00	0.	:
60.00 - 66.00	0.	:
66.00 - 72.00	0.	:
72.00 - 78.00	0.	:
78.00 - 84.00	0.	:
84.00 - 90.00	0.	:

FIELD COUNT vs

PERCENT AREA

HISTOGRAM

AVE % AREA =

40.630

Table 3: DISTRIBUTION OF FEATURE1 COUNT vs CALC.C

Cambridge Instruments      QUANTIMET 970 QUIPS: V08.00 USER:  
 ROUTINE : CONWID      SPECIMEN : .6 OSY WW SB LAMINAT

5

Total FEATURE1 COUNT = 11064. Mean = 23.9 Std Dev =  
 11.2  
 Undersize Count = 0      Oversize Count = 0.

CALC.C  
 (MICRONS)

LIMITS	COUNT	(COUNT )
1.00 - 1.58	0.	:
1.58 - 2.51	0.	:
2.51 - 3.98	0.	:
3.98 - 6.31	0.	:
6.31 - 10.00	481	:****
10.00 - 15.85	2575	:*****
15.85 - 25.12	3690	:*****
25.12 - 39.81	3360	:*****
39.81 - 63.10	888	:*****
63.10 - 100.00	69	:
100.00 - 158.49	1	:
158.49 - 251.19	0.	:
251.19 - 398.11	0.	:
398.11 - 630.96	0.	:
630.96 - 1000.00	0.	:

PORE COUNT VS  
 CON WIDTH (um)

10

Table 4: DISTRIBUTION OF FEATURE1 AREA vs CALC.C

Cambridge Instruments      QUANTIMET 970 QUIPS: V08.00 USER:  
 ROUTINE : CONWID      SPECIMEN : .6 OSY WW SB LAMINAT

5

Total FEATURE1 AREA = 36296340.      Mean = 32.1 Std  
 Dev = 11.9  
 Undersize Count = 0      Oversize Count = 0.

10 CALC.C (MICRONS )

LIMITS		AREA (SQ MICRONS)	
100. -	1.58	0.	:
1.58 -	2.51	0.	:
2.51 -	3.98	0.	:
3.98 -	6.31	0.	:
6.31 -	10.00	72203.47000	:
10.00 -	15.85	1240307.000	::**
15.85 -	25.12	9073056.	:*****
25.12 -	39.81	18701750.	:*****
39.81 -	63.10	6430334.000	:*****
63.10 -	100.00	747591.8000	:
100.00	158.49	31182.57000	:
-			
158.49	251.19	0.	:
-			
251.19	398.11	0.	:
-			
398.11	630.96	0.	:
-			
630.96	1000.00	0.	:
-			

CUM PORE A% VS  
 CON WIDTH (um)

Table 5: DISTRIBUTION OF COUNT vs ANISOT

5 Cambridge Instruments QUANTIMET 970 QUIPS: V08.00 USER:  
 ROUTINE : CONWID SPECIMEN : .6 OSY WW SB LAMINAT

Total ANISOT = 18.4000 Mean = 0.767 Std  
 Dev = 0.0917  
 Undersize Count + 0 Oversize Count = 0.

10

ANISOT (UNITS)	COUNT
0. - 0.10	0. :
0.10 - 0.20	0. :
0.20 - 0.30	0. :
0.30 - 0.40	0. :
0.40 - 0.50	0. :
0.50 - 0.60	1. :***
0.60 - 0.70	4. :*****
0.70 - 0.80	10. :*****
0.80 - 0.90	8. :*****
0.90 - 1.00	1. :***
1.00 - 1.10	0. :
1.10 - 1.20	0. :
1.20 - 1.30	0. :
1.30 - 1.40	0. :
1.40 - 1.50	0. :

% OF FIELDS vs  
 ANISOTROPY

AVERAGE PORE 0.77534  
 ANISOTROPY (TAN THETA)  
 =

TOTAL  
 SCANNED AREA 0.52659 SQ CM  
 =

Table 6: DISTRIBUTION OF COUNT vs PERCAREA

Cambridge Instruments QUANTIMET 970QUIPS/MX: V08.00 USER:  
 ROUTINE: CONWID SPECIMEN : 2.0 OSY PUB

5

Total PERCAREA = 978. Mean = 40.8 Std Dev = 7.18  
 Undersize Count = 0 Oversize Count = 0.

PERCAREA LIMITS	(% AREA COUNT)	
0. - 6.00	0.	:
6.00 - 12.00	0.	:
12.00 - 18.00	0.	:
18.00 - 24.00	0.	:
24.00 - 30.00	1.	:*****
30.00 - 36.00	6.	:*****
36.00 - 42.00	6.	:*****
42.00 - 48.00	8.	:*****
48.00 - 54.00	2.	:*****
54.00 - 60.00	1.	:*****
60.00 - 66.00	0.	:
66.00 - 72.00	0.	:
72.00 - 78.00	0.	:
78.00 - 84.00	0.	:
84.00 - 90.00	0.	:

FIELD COUNT vs PERCENT  
 AREA HISTOGRAM

AVE %  
 AREA 40.665  
 =

10

Table 7: DISTRIBUTION OF FEATURE1 COUNT vs CALC.C

Cambridge Instruments QUANTIMET 970 QUIPS/MX: V08.00 USER:  
 ROUTINE : CONWID SPECIMEN : 2.0 OSY PUB

5

Total FEATURE1 COUNT = 2147. Mean = 25.2 Std Dev =  
 17.3

Undersize Count = 0 Oversize Count = 0.

10

CALC.C LIMITS	(MICRONS COUN (COUNT) T		
1.00 -	1.58	0.	:
1.58 -	2.51	0.	:
2.51 -	3.98	0.	:
3.98 -	6.31	0.	:
6.31 -	10.00	221.	:*****
10.00 -	15.85	667.	:*****
15.85 -	25.12	421.	:*****
25.12 -	39.81	489.	:*****
39.81 -	63.10	267.	:*****
63.10 -	100.00	73.	:***
100.00	158.49	8.	:
-			
158.49	251.19	1.	:
-			
251.19	398.11	0.	:
-			
398.11	630.96	0.	:
-			
630.96	1000.00	0.	:
-			

PORE COUNT VS  
 CON WIDTH (um)

Table 8: DISTRIBUTION OF FEATURE1 AREA vs CALC.C

Cambridge Instruments      QUANTIMET 970 QUIPS: V08.00 USER :  
 ROUTINE : CONWID      SPECIMEN : 2.0 OSY PUB

5

Total FEATURE1 AREA      =      40203880.      Mean = 36.4  
 Std Dev = 15.7  
 Undersize Count      =      0      Oversize Count =      0.

10

CALC.C (MICRONS )

LIMITS	AREA	(SQ MICRONS)
1.00 - 1.58	0.	:
1.58 - 2.51	0.	:
2.51 - 3.98	0.	:
3.98 - 6.31	0.	:
6.31 - 10.00	49332.1600	:
	0	
10.00 - 15.85	578338.600	:*
	0	
15.85 - 25.12	6682890.	:*****
25.12 - 39.81	21962620.	:*****
39.81 - 63.10	8517650.	:*****
63.10 - 100.00	2113692.00	:***
	0	
100.00 - 158.49	257262.800	:
-	0	
158.49 - 251.19	42126.7500	:
-	0	
251.19 - 398.11	0.	:
-		
398.11 - 630.96	0.	:
-		
630.96 - 1000.0	0.	:
-	0	

CUM PORE A% VS  
 CON WIDTH (um)



Table 9: DISTRIBUTION OF COUNT vs ANISOT

Cambridge Instruments QUANTIMET 970 QUIPS: V08.00 USER:  
 ROUTINE : CONWID SPECIMEN : 2.0 OSY PUB

5 Total ANISOT = 26.5500 Mean = 1.15 Std Dev =  
 0.212  
 Undersize Count + 0 Oversize Count = 1.

10 ANISOT (UNITS )  
 LIMITS COUNT

0. -	0.10	0.	:
0.10 -	0.20	0.	:
0.20 -	0.30	0.	:
0.30 -	0.40	0.	:
0.40 -	0.50	0.	:
0.50 -	0.60	0.	:
0.60 -	0.70	1.	:*****
0.70 -	0.80	0.	:
0.80 -	0.90	2.	:*****
0.90 -	1.00	2.	:*****
1.00 -	1.10	3.	:*****
1.10 -	1.20	5.	:*****
1.20 -	1.30	5.	:*****
1.30 -	1.40	1.	:*****
1.40 -	1.50	4.	:*****

# OF FIELDS vs  
 ANISOTROPY

AVERAGE PORE  
 ANISOTROPY (TAN THETA)  
 = 1.171

TOTAL  
 SCANNED AREA 0.52659 SQ CM  
 =

The convoluted width (Conwid) of a pore in the non-woven material, analyzed using the CONWID routine, is the average width of a pore independent of the convolution, shape, orientation or protrusion of the fibers or other element defining the pore. The CONWID routine provides analysis and data, including histograms, on the number of pores, and the average coverage (%A) and pore-wide data, both count and area-weighted. For example, in comparing Tables 2 and 6, it can be seen that the spunbond laminate material has a similar average %area as the PUB material, but that the PUB material has a greater standard deviation. In comparing Tables 3 and 7, it can be seen that the spunbond laminate material has much greater total pore count (11064) versus the PUB material (2147), and with only a slightly smaller average pore size. In comparing Tables 4 and 8, it can be seen that the spunbond laminate material has a slightly lesser total pore area than the PUB material. Finally, Tables 5 and 9 compare the anisotropic properties of the spunbond laminate material and the PUB material, where it can be observed that the PUB material has a greater mean anisotropy than the spunbond laminate material.

As shown in Tables 10 and 11, a fuzz-on-edge test, which is an image analysis test, was also used to analyze the spunbond laminate material versus the PUB material. The fuzz-on-edge test measures the intensity of protruding fiber loft in perimeter length per unit-edge length.

The image analysis data are taken from two glass plates made into one fixture. Each plate has a sample folded over the edge with the sample folded in the CD direction and placed over the glass plate. The edge is beveled to 1/16" thickness. The testing method and equipment is further described and disclosed in U.S. Provisional Application No. 60/204,083, filed May 12, 2000, the entire disclosure of which is hereby incorporated herein by reference. For example, in one sequence, the glass plates have a thickness of ¼ inch, each having a beveled edge with a thickness of 1/16 inch. During the testing, samples are placed over the beveled edges. Multiple images of the folded edges are then

taken along the edge. Thirty (30) files of view are examined on each folded edge to provide a total of sixty (60) files of view. Each edge is about 6.5 mm in height. Each view has a Fuzz-On-Edge (FOE) or "PR/EL" value measured before and after removal of protruding fibers. PR/EL is the perimeter per

5 edge-length examined in each filed of view. In particular, PR is the perimeter around the protruding fibers, and EL is the length of the measure sample. The PR/EL values are averaged and assembled into a histogram, shown in Tables 10 and 11. The analysis is completed and the data obtained using the

QUANTIMET 970 Image Analysis System described above using standard

10 conditions with a 60-mm Micro-Mikkor lens. The QUIPS routine for performing this work is designated as FUZZ10, and is set forth at Appendix 2.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201

Table 10: DISTRIBUTION OF COUNT vs PROVEREL

Cambridge Instruments      QUANTIMET 970 QUIPS: V08.02 USER:  
 ROUTINE : FUZZIO          SPECIMEN : .6 OSY WW SB LAMINAT

5 AVE PR-OVER-EL (UM/UM) = 0.36932

TOTAL NUMBER OF FIELDS = 60.

FIELD HEIGHT (HM) = 6.087

10

Total PROVEREL = 22.5000 Mean = 0.375 Std Dev =  
 0.460

Undersize Count = 0. Oversize Count = 0.

15

PROVEREL (HM/MH )  
 LIMITS                      COUNT

0. -	0.25	35.	*****
0.25 -	0.50	14.	*****
0.50 -	0.75	4.	****
0.75 -	1.00	1.	.*
1.00 -	1.25	2.	.**
1.25 -	1.50	1.	.*
1.50 -	1.75	1.	.*
1.75 -	2.00	0.	:
2.00 -	2.25	2.	.**
2.25 -	2.50	0.	:
2.50 -	2.75	0.	:
2.75 -	3.00	0.	:
3.00 -	3.25	0.	:
3.25 -	3.50	0.	:
3.50 -	3.75	0.	:
3.75 -	4.00	0.	:
4.00 -	4.25	0.	:
4.25 -	4.50	0.	:
4.50 -	4.75	0.	:
4.75 -	5.00	0.	:

Table 11: DISTRIBUTION OF COUNT vs PROVEREL

Cambridge Instruments      QUANTIMET 970 QUIPS: V08.02USER  
 ROUTINE : FUZZIO            SPECIMEN : 2.0 OSY PUB

5    AVE PR-OVER-EL (UM/UM) = 0.92355

TOTAL NUMBER OF FIELDS = 60.

FIELD HEIGHT (HM) = 6.087

10

Total PROVEREL = 55.500    Mean = 0.925    Std Dev =  
 0.614

Undersize Count = 0.    Oversize Count = 0.

15

PROVEREL (HM/MH )

LIMITS	COUNT	
0. - 0.25	5.	:*****
0.25 - 0.50	9.	:*****
0.50 - 0.75	11.	:*****
0.75 - 1.00	15.	:*****
1.00 - 1.25	4.	:*****
1.25 - 1.50	11.	:*****
1.50 - 1.75	1.	:**
1.75 - 2.00	1.	:**
2.00 - 2.25	0.	:
2.25 - 2.50	2.	:*****
2.50 - 2.75	0.	:
2.75 - 3.00	0.	:
3.00 - 3.25	0.	:
3.25 - 3.50	0.	:
3.50 - 3.75	1.	:**
3.75 - 4.00	0.	:
4.00 - 4.25	0.	:
4.25 - 4.50	0.	:
4.50 - 4.75	0.	:
4.75 - 5.00	0.	:

As can be seen when comparing Tables 10 and 11, the average PR/EL  
 (.37) for the spunbond laminate material is less than the PR/EL average (.92)  
 20 for the PUB material. Likewise, the total PR/EL (22.5) for the spunbond  
 laminate was less than the total PR/EL (55.5) for the PUB material.

Preferably, the non-woven material used for the body panels will have an average PR/EL less than .75, more preferably less than .60 and even more preferably less than 0.50. Preferably, the non-woven material used for the body panels will have a total PR/EL less than 50.0, more preferably less than 35.0 and even more preferably less than 25.0.

Referring to FIGS. 1-3, fastening members or tabs **42** are attached and extend laterally inboard from the outboard side edge **24** of the front body panel **4** from an attachment location **45**. The front body panel **4** includes a middle portion **33**, or landing member, and opposite side portions **35**. Opposite longitudinally extending lines of weakness **37** separate the middle, landing member portion from the opposite side portions, such that the side portions are initially breakably attached to opposite sides of the landing member portion. The lines of weakness **37** can comprise a perforation or other series of cuts that allow a user or the manufacturer to separate the side portions from the middle portion. For example, the absorbent garment can be broken after the garment is applied to a user, or beforehand. Preferably, the fastening members **42** are secured to the garment-side surface of the side portions **35** between the side edge **24** of the front body panel and the line of weakness **35**.

It should be understood that in other embodiments the fastening members can be secured to the rear body panel and engage the front body panel or, conversely, can be secured to the front body panel and engage the rear body panel, preferably along at least a portion that is not elasticized. Preferably, the fastening members are fixedly secured to the outer, garment-side surface of the front and/or rear body panels, and releasably engage the outer, garment-side surface of the front and/or rear body panels, although it should be understood that the fastening members could be fixedly secured to an inner body-side surface of front and/or rear body panels and releasably engage an inner, body-side surface of the front and/or rear body panels.

The opposite side edges **24** of the front body panel **4** are joined to the opposite side edges **28** of the rear body panel **6** to form a seam **39**, which has a longitudinal length (SSL), which may be the same as or less than the lengths (FPL) and (RPL) of either of the front and rear body panels. In this way, prior to the breaking of the line of weakness **37**, the absorbent garment can be configured as a pant-like garment, which can be pulled over the legs of the user. After the garment is applied to the user, the lines of weakness can be broken, if desired, or left intact, as the fasteners are adjusted to fit the garment to the user. If desired, the lines of weakness can be broken prior to securing the garment to the user, for example when the user is bed-ridden. In this configuration, the garment is laid beneath the user and is secured to the user with the fastening tabs. By providing the side portions, and by connecting the fastening tabs to the front panel, instead of the rear body panel, the tabs are located at the front of the user so as to not provide discomfort to the user when lying on their backs.

It should be understood that the front and rear body panels can be made as a unitary member that extends along the crotch from the front to back and with the sides thereof connected to form side seams. Alternatively, the front and rear body panels can be formed integrally, for example as one panel extending around the waist and hips of the user.

Preferably, as shown in FIGS. 1-3, 10 and 11, the fastening members **42** comprise a carrier member **43** that is formed in a generally side-ways, "U" shape, with a vertical extending base member **55** and a pair of laterally extending and longitudinally spaced tab members **47**. The carrier member could also comprise one or more than two tab members. The carrier members are preferably fixedly secured to the side portions of the body panel **4** with adhesive bonds **49**, sonic bonds, thermal bonds, pinning, stitching or other known types of attachment, as shown for example in FIGS. 2-6 and 11. In alternative embodiments, the fastening members can be fixedly secured to the

rear panel, as shown in FIG. 9, or to one or both of the front and rear panels, *e.g.*, at the seam, as shown for example in FIG. 10.

Each carrier member **43** has a longitudinal length (TL). Each of the tab members **47** comprises an engagement portion having a longitudinal length (FTL), as shown in FIGS. 10 and 11. The combined longitudinal length of the engagement portions of the two tab members is defined as an engagement length (ET). For example, in the embodiments shown in FIGS. 9-11,  $ET = FTL1 + FTL2$ . The engagement portion preferably comprises an array of hooks, as explained below, but alternatively can comprise various adhesives, such as pressure sensitive adhesives, buttons, zippers and other releasable and reattachable fastening devices.

In one embodiment, shown in FIG. 9, each fastening member **42** is comprised of two separate, longitudinally spaced tab members **47**, each having a length (TTL) and an engagement portion having a length (FTL), with TTL preferably being substantially the same as FTL. The length of the fastening member (TL) is defined as the sum of length of the tab members (TTL), and the engagement length (ET) is equal to the sum of the lengths of the engagement portions FTL.

In any of the embodiments, the two or more tab members provides a pant like fit that controls the waist and leg openings in the front and back of the garment, and also allows the user to adjust the fit of the garment without totally undoing the garment. For example, the user can release one of the tab members and refasten it without undoing the other tab member.

Referring to FIGS. 9-11, the preferred ratio of the engagement length ET to the front panel length FPL is at least about 20%, and more preferably the engagement length ET is at least about 30% of the front panel length FPL, and most preferably is at least about 40% of the front panel length. Preferably the engagement length ET is less than about 90% of the front panel length FPL, and more preferably the engagement length ET is less than about 80% of the



front panel length FPL, and most preferably is less than about 60% of the front panel length.

In addition, the fastener length TL is preferably at least about 50% of the side seam length SSL, and more preferably is at least about 70% of the side seam length SSL and most preferably is at least about 90% of the side seam length. The fastener length TL is also preferably at least about 50% of the front panel length FPL, and more preferably is at least about 70% of the front panel length FPL, and most preferably is at least about 90% of the front panel length FPL. Likewise, the fastener length TL is preferably at least about 50% of the length of the outboard edge of the rear body panel RPL, and more preferably is at least about 70% of the length of the outboard edge of the rear body panel RPL, and most preferably is at least about 90% of the length of the outboard edge of the rear body panel RPL.

A hook-type fastener member **51**, or hook strip, is secured to the carrier member **43** with adhesive, ultrasonic bonding, stitching or other known attachment devices. The end portion **53** or tip of the carrier member can be left uncovered by the fastener member **51**, such that it can be lifted or flexed and grasped by a user as they disengage or peel back the fastener member. It should be understood that the term "hook" as used herein means any element capable of engaging another element, and is not intended to limit the form of the engaging elements, for example to include only "hooks," but rather encompasses any form shape of engaging element, whether unidirectional or bi-directional. Various hook configurations are described in U.S. Patent No. 5,845,375 to Miller et al., U.S. Patent No. 6,132,660 to Kampf, U.S. Patent No. 6,000,106 to Kampf, U.S. Patent No. 5,868,987 to Kampf, U.S. Patent No. 4,894,060 to Nestegard, and U.S. Patent No. 6,190,594 B1 to Gorman, the entire disclosures of which are incorporated by reference herein. Some examples of suitable hook fasteners are the various CS600 hook fasteners manufactured by Minnesota Mining and Manufacturing Co., St. Paul Minn.

In one preferred embodiment, a mushroom-type hook strip comprises a homogeneous backing **57** of thermoplastic resin and, integral with backing, an array **59** of upstanding stems **61** distributed across at least one face of the backing, each having a mushroom head **63**. The array of hooks on each strip  
 5 comprise an engagement portion having a longitudinal length (FTL). The stems can have a molecular orientation as evidenced by a birefringence value of at least 0.001, and the mushroom heads having circular disc shapes with generally planar end surfaces opposite the backing, which disc shaped heads preferably have diameter to thickness ratios of greater than about 1.5 to 1.

10 The stems **61** of the hook strip can be molecularly orientated as evidenced by a birefringence value of at least 0.001. As such, they have significantly greater stiffness and durability, as well as greater tensile and flexural strength, than would be achievable without such orientation. Because of these qualities, the portions of the stems not heated by a heating surface during  
 15 the forming process remain resiliently flexible during a deforming step, which preferably involves the application of heat to the stem tips by contact with the heated surface of a metal roller. Such contact forms the tip of each stem into a circular disc shaped mushroom head at the tip of each stem, which head has a substantially flat inner surface that enhances its holding power when engaged  
 20 with a loop.

As compared to hook strips that have unoriented stems, the enhanced strength of the hooks of the hook strip makes them less likely to break during disengagement. When the hook strip is used with the non-woven material herein described, the enhanced strength of the hooks makes them less likely to break  
 25 under disengagement forces than the fibers of the material, a beneficial attribute for at least two reasons. First, broken hooks can create debris whereas a broken fiber typically does not. Furthermore, the non-woven material typically contains many more engageable fibers than there are hooks per unit area, thus allowing a greater number of disengagements before a hook-and-loop fastener becomes  
 30 useless.

Although the stems of the hook strip preferably are generally circular in cross section, other suitable cross sections include rectangular and hexagonal. The stems preferably have fillets at their bases, both to enhance strength and stiffness and for easy release from a mold in which they are formed. In addition, the stems can be tapered, preferably from a larger to a smaller cross-section as one moves from the base to the head.

The stem portions are preferably at an angle of about 90 degrees from the backing substrate, however, this angle can range from about 80 to about 100 degrees, preferably 85 to about 95 degrees. The hook head portion is formed on the distal end of the stem. The hook head can be elongated in on or more directions forming the fiber engaging portions. These fiber engaging portions extend outward from the stem portion at any angle so that they can project upwardly away from the film backing, parallel with the film backing or even downward toward the film backing.

For example, as shown in FIG. 8, the hook head portion has a deformed fiber engaging portion that projects downward. Preferably, the lower surface of the fiber engaging portion also projects downward form a crook between the lower face of the fiber engaging portion and the stem base portion. In one preferred embodiment, the heads of the hooks generally project at a downward angle from the hook head top portions toward the base. This downward angle (measured from a reference line taken from the top of the hook head and parallel with the backing) is generally from about 0 to about 70 degrees, preferably from about 5 to about 60 degrees and most preferably from about 5 to about 35 degrees (defined by a linear extent running from a center region of the hook head top portion to an end of the hook head fiber engaging portion).

The head shape with its high diameter to thickness ratio, and the small size and close spacing or high density of individual hooks that are provided by the hook strip according to the present invention makes it able to easily firmly releasably engage non-woven materials in shear, possibly because the many thin heads can easily move radially into engagement with rather small fibers. Thus

the hook strip is particularly useful for hook-and-loop fastening when the "loops" are provided by non-woven materials which are not particularly adapted for use as the loop portions of hook and loop fasteners, and which are not as well engaged by known prior art hook strips. For example, the hook strip is particularly well-suited for engaging the topographically flatter non-woven materials described above, including the non-woven spunbond material, which has relatively fewer loose, outwardly extending, free fibers than conventional loop materials, but still provides a relatively high number of pores, of sufficient size, such that the material can be engaged by the hooks. Indeed, once the hooks are received in the pores, or embedded in the non-woven material, the fastening tabs provide excellent shear characteristics, such that the garment is securely fastened during normal wearing conditions.

In general, the hooks are of uniform height, preferably of from about 0.10 to 1.30 mm in height, and more preferably from about 0.18 to 0.51 mm in height; have a density on the backing preferably of from 60 to 1,600 hooks per square centimeter, and more preferably from 125 to 690 hooks per square centimeter, and preferably greater than about 150 hooks per square centimeter; have a stem diameter adjacent the heads of the hooks preferably of from 0.07 to 0.7 mm, and more preferably from about 0.1 to 0.3 mm. The deformed hook heads project radially past the stems on at least one side preferably by an average of about 0.01 to 0.3 mm, and more preferably by an average of about 0.02 to 0.25 mm and have average thicknesses between their outer and inner surfaces (i.e., measured in a direction parallel to the axis of the stems) preferably of from about 0.01 to 0.3 mm and more preferably of from about 0.02 mm to 0.1 mm. The hook heads have average head diameter (i.e., measured radially of the axis of the heads and stems) to average head thickness ratio preferably of from 1.5:1 to 12:1, and more preferably from 2.5:1 to 6:1.

For most hook-and-loop uses, the hooks of the hook strip should be distributed substantially uniformly over the entire area of the hook strip, usually in a square or hexagonal array.

To have both good flexibility and strength, the backing of the hook strip preferably is from 0.02 to 0.5 mm thick, and more preferably is from 0.06 to 0.3 mm in thick, especially when the hook strip is made of polypropylene or a copolymer of polypropylene and polyethylene. For some uses, a stiffer backing  
 5 could be used, or the backing can be coated with a layer of pressure sensitive adhesive on its surfaces opposite the hooks by which the backing could be adhered to a substrate, such as the carrier member **43**, so that the backing could then rely on the strength of the substrate to help anchor the hooks.

Virtually any orientable thermoplastic resin that is suitable for extrusion  
 10 molding may be used to produce the hook strip. Thermoplastic resins that can be extrusion molded and should be useful include polyesters such as poly(ethylene terephthalate), polyamides such as nylon, poly(styrene-acrylonitrile), poly(acrylonitrile-butadiene-styrene), polyolefins such as polypropylene, and plasticized polyvinyl chloride. One preferred thermoplastic  
 15 resin is a random copolymer of polypropylene and polyethylene containing 17.5% polyethylene and having a melt flow index of 30, that is available as SRD7-463 from Shell Oil Company, Houston, Tex.

Referring to FIG. 8, the hook strip is shown as having a substantially continuous planar backing **57** of thermoplastic resin. Integral with the backing  
 20 is an array **59** of hooks **65** projecting generally at right angles to one major surface of the backing. Each of the hooks **65** has a stem **61**, and, at the end of the stem opposite the backing, a generally circular plate-like cap or head projecting radially past or overhanging the stem so as to form a fiber engaging portion **63** that projects downward. Preferably, the lower surface of the fiber  
 25 engaging portion **63** also projects downward form a crook between the lower face of the fiber engaging portion and the stem base portion. The stem **61** can also have a fillet around its base.

When the absorbent garment is secured to the user, the fastening tabs **42**  
 30 secured to the side portions of the front body panels **4** releasably engage or are otherwise connected to the middle landing member portion of the body panels

4. Preferably, at least a portion of the array of hooks **65** engage the non-elasticized area of the middle portion. In particular, the heads on the hooks engage the fibers in the non-woven spunbond material without the need to provide additional loops or otherwise alter the material. It should be
- 5 understood however, that a portion of the array of hooks **65** can engage the elasticized areas. For example, a portion of the array of hooks on the upper tab member may engage a portion of the elasticized area along the waist portion of the front panel, while a portion of the hooks on the lower tab member may engage a portion of the elasticized area along the leg opening of the garment.
- 10 The landing member portion of the front body panel member can also be configured with an additional material, or landing patch, secured to the garment side thereof and which comprises a loop material.

- Referring again to FIGS. 1-4, the absorbent garment includes an absorbent composite **50** having first and second longitudinally opposed terminal
- 15 end edges **60**, **62**. The absorbent composite includes a substantially liquid permeable topsheet **64**, or liner, and a substantially liquid impermeable backsheet **68**, or outer cover. A retention portion **70** is disposed or sandwiched between the topsheet and the backsheet, which are connected. The topsheet, backsheet and other components of the absorbent composite **50** can be joined
- 20 for example with adhesive bonds **77**, sonic bonds, thermal bonds, pinning, stitching or any other attachment techniques known in the art, as well as combinations thereof. For example, a uniform continuous layer of adhesive, a patterned layer of adhesive, a sprayed pattern of adhesive or any array of lines, swirls or spots of construction bonds may be used to join the topsheet and
- 25 backsheet, or any of the other components described herein.

Additional layers, including for example, a surge layer **72**, are also preferably incorporated into the absorbent composite. Preferably, the surge layer does not run the entire length of the absorbent composite and is shorter than the retention portion. The topsheet can be indirectly joined to the

backsheet by affixing the topsheet to intermediate layers, such as the surge layer or retention portion, which in turn is affixed to the backsheet.

The backsheet 68 is preferably liquid impermeable, but may be liquid permeable, e.g., when an additional barrier layer is used with the retention portion. For example, in one embodiment, the backsheet can be made from a thin plastic film, or other flexible, substantially liquid-impermeable material. As used herein, the term "flexible" means a material that is compliant and which will readily conform to the general shape and contour of the body of the user. The backsheet prevents various bodily fluids and exudates from wetting or otherwise contaminating various bedding or outer garments worn by the user over the absorbent garment. In particular, the backsheet can include a film, such as a polyethylene film, having a thickness of from about 0.012 mm to about 0.051 mm.

In various constructions, the topsheet can comprise various woven or nonwoven materials. For example, the topsheet can be composed of a meltblown or spunbonded web of desired fibers, and may also be a bonded-carded web. For example, the topsheet can be made of a substantially hydrophobic material, and the hydrophobic material may optionally be treated with a surfactant or otherwise processed to impart a desired level of wettability and hydrophilicity. In one particular embodiment of the invention, the topsheet is a nonwoven, spunbond polypropylene fabric composed of about 2.8 - 3.2 denier fibers formed into a web having a basis weight of about 22 gsm and density of about 0.06 gm/cc. The fabric can be surface treated with an operative amount of surfactant, such as about 0.28% Triton X-102 surfactant. The surfactant can be applied by any conventional means, such as spraying, printing, brush coating or the like.

In various constructions, the backsheet can comprise a woven or nonwoven fibrous web layer, which is treated or constructed, partially or wholly, to impart the desired levels of liquid impermeability to selected regions that are adjacent to or proximate the absorbent retention portion. For example,

the backsheet may include a gas-permeable, nonwoven fabric layer laminated to a polymer film layer which may or may not be gas-permeable. Other examples of fibrous, cloth-like backsheet materials can comprise a stretch thinned or stretch thermal laminate material composed of a 0.6 mil (0.015 mm) thick polypropylene cast film and a 0.7 ounce per square yard (23.8 gsm) polypropylene spunbond material (2 denier fibers). A material of this type has been employed to form the outercover of a HUGGIES® Ultratrim Disposable Diaper, which has been commercially available from Kimberly-Clark Corporation. The backsheet typically provides the outercover of the article. Optionally, however, the article may include a separate outercover component member which is additional to the backsheet. The outercover can be joined, for example, to one or more of the absorbent composite and/or body panels.

The backsheet may include a micro-porous, "breathable" material which permits gases, such as water vapor, to escape from the absorbent garment while substantially preventing liquid exudates from passing through the backsheet. For example, the breathable backsheet may be composed of a microporous polymer film or a nonwoven fabric which has been coated or otherwise modified to impart a desired level of liquid impermeability. For example, a suitable microporous film can be a PMP-1 material, which is available from Mitsui Toatsu Chemicals, Inc., a company having offices in Tokyo, Japan; or an XKO-8044 polyolefin film available from 3M Company of Minneapolis, Minnesota. The backsheet may also be embossed or otherwise provided with a pattern or matte finish to exhibit a more aesthetically pleasing appearance.

In various configurations of the invention, where a component, such as the backsheet is configured to be permeable to gas while having a resistance and limited permeability to aqueous liquid, the liquid resistant component can have a construction which is capable of supporting a selected hydrohead of water substantially without leakage therethrough. A suitable technique for determining the resistance of a material to liquid penetration is Federal Test Method Standard FTMS 191 Method 5514, 1978, or an equivalent thereof.



In one preferred embodiment, the backsheet is sufficiently impermeable to liquid and semi-liquid materials to substantially prevent the undesired leakage of waste materials, defined as exudates, including for example urine and feces. For example, the backsheet member can desirably support a hydrohead of at least about 45 centimeters (cm) substantially without leakage. The backsheet member can alternatively support a hydrohead of at least about 55 cm, and optionally, can support a hydrohead of at least about 60 cm, or more, to provide improved benefits.

The backsheet also can be extensible. In one preferred embodiment, the backsheet is capable of providing an elongation of at least about 1 cm when subjected to a tensile force of 11.8 g/cm, and further provides a substantially permanent deformation of at least about 20% when subjected to a tensile force of 19.70 g/cm and is then allowed to relax under a zero applied stress for a period of 1 minute.

For example, the extensible backsheet can be composed of a necked fiber, a creped fiber, a micro-pleated fiber, polymer films or the like, as well as combinations thereof. The fabrics may be woven or nonwoven materials, such as spunbond fabrics. One example of a suitable extensible material is a 60% necked, polypropylene spunbond having a basis weight of about 1.2 osy.

The backsheet also can be expandable, for example when it has one or more folds, e.g., one or more z-folds (not shown), or can be both extensible and expandable. The term expandable as used herein means to enlarge or to increase the extent or area, lateral and/or longitudinal, thereof, e.g., by unfolding one or more folds.

The retention portion **70** is preferably made of an absorbent material, which tends to swell or expand as it absorbs liquid excreted or exuded by the user. For example, the absorbent material can be made of airformed, airlaid and/or wetlaid composites of fibers and high absorbency materials, referred to as superabsorbents. Superabsorbents typically are made of polyacrylic acids, such as FAVOR 880 available from Stockhausen, Inc. of Greensboro, North

Carolina. The fibers can be fluff pulp materials, such as Alliance CR-1654, or any combination of crosslinked pulps, hardwood, softwood, and synthetic fibers. Airlaid and wetlaid structures typically include binding agents, which are used to stabilize the structure. In addition, various foams, absorbent films, and superabsorbent fabrics can be used as an absorbent material.

In one preferred embodiment, an absorbent material is made of fibrous absorbent materials with a relatively high internal integrity, including for example one made with thermoplastic binder fibers in airlaid absorbents, e.g., pulp, bicomponent binding fibers, and superabsorbents, which have higher densities in the folded regions. The higher density and resulting smaller capillary size in these regions promotes better wicking of the liquid. Better wicking, in turn, promotes higher utilization of the absorbent material and tends to result in more uniform swelling throughout the absorbent material as it absorbs the liquid.

Various types of wettable, hydrophilic fibrous material can be used to form the component parts of absorbent, and particularly the retention portion 70. Examples of suitable fibers include naturally occurring organic fibers composed of intrinsically wettable material, such as cellulosic fibers; synthetic fibers composed of cellulose or cellulose derivatives, such as rayon fibers; inorganic fibers composed of an inherently wettable material, such as glass fibers; synthetic fibers made from inherently wettable thermoplastic polymers, such as particular polyester or polyamide fibers; and synthetic fibers composed of a nonwetable thermoplastic polymer, such as polypropylene fibers, which have been hydrophilized by appropriate means. The fibers may be hydrophilized, for example, by treatment with silica, treatment with a material which has a suitable hydrophilic moiety and is not readily removable from the fiber, or by sheathing the nonwetable, hydrophobic fiber with a hydrophilic polymer during or after the formation of the fiber. For the purposes of the present invention, it is contemplated that selected blends of the various types of fibers mentioned above may also be employed.

As used herein, the term "hydrophilic" describes fibers or the surfaces of fibers which are wetted by the aqueous liquids in contact with the fibers. The degree of wetting of the materials can, in turn, be described in terms of the contact angles and the surface tensions of the liquids and materials involved.

5 Equipment and techniques suitable for measuring the wettability of particular fiber materials or blends of fiber materials can be provided by a Cahn SFA-222 Surface Force Analyzer System, or a substantially equivalent system. When measured with such system, fibers having contact angles less than  $90^\circ$  are designated "wetable", while fibers having contact angles greater than  $90^\circ$  are  
10 designated "nonwetable".

In particular arrangements, the retention portion of the absorbent may comprise a mixture of superabsorbent hydrogel-forming particles and synthetic polymer meltblown fibers, or a mixture of superabsorbent particles with a fibrous coform material comprising a blend of natural fibers and/or synthetic  
15 polymer fibers. The superabsorbent particles may be substantially homogeneously mixed with the hydrophilic fibers, or may be nonuniformly mixed. For example, the concentrations of superabsorbent particles may be arranged in a non-step-wise gradient through a substantial portion of the thickness (z-direction) of the absorbent structure, with lower concentrations  
20 toward the bodyside of the absorbent composite and relatively higher concentrations toward the outside of the absorbent structure. Suitable z-gradient configurations are described in U.S. Patent No. 4,699,823 issued October 13, 1987 to Kellenberger et al., the entire disclosure of which is incorporated herein by reference in a manner that is consistent (not in conflict)  
25 with the present description. Alternatively, the concentrations of superabsorbent particles may be arranged in a non-step-wise gradient, through a substantial portion of the thickness (z-direction) of the absorbent structure, with higher concentrations toward the bodyside of the absorbent composite and relatively lower concentrations toward the outside of the absorbent structure.  
30 The superabsorbent particles may also be arranged in a generally discrete layer

within the matrix of hydrophilic fibers. In addition, two or more different types of superabsorbent may be selectively positioned at different locations within or along the fiber matrix.

The high-absorbency material may comprise absorbent gelling materials, such as superabsorbents. Absorbent gelling materials can be natural, synthetic and modified natural polymers and materials. In addition, the absorbent gelling materials can be inorganic materials, such as silica gels, or organic compounds such as cross-linked polymers. The term "cross-linked" refers to any means for effectively rendering normally water-soluble materials substantially water insoluble but swellable. Such means can include, for example, physical entanglement, crystalline domains, covalent bonds, ionic complexes and associations, hydrophilic associations, such as hydrogen bonding, and hydrophobic associations or Van der Waals forces.

Examples of synthetic absorbent gelling material polymers include the alkali metal and ammonium salts of poly(acrylic acid) and poly (methacrylic acid), poly(acrylamides), poly(vinyl ethers), maleic anhydride copolymers with vinyl ethers and alpha-olefins, poly(vinyl pyrrolidone), poly(vinylmorpholinone), poly(vinyl alcohol), and mixtures and copolymers thereof. Further polymers suitable for use in the absorbent composite include natural and modified natural polymers, such as hydrolyzed acrylonitrile-grafted starch, acrylic acid grafted starch, methyl cellulose, chitosan, carboxymethyl cellulose, hydroxypropyl cellulose, and the natural gums, such as alginates, xanthan gum, locust bean gum and the like. Mixtures of natural and wholly or partially synthetic absorbent polymers can also be useful in the present invention. Other suitable absorbent gelling materials are disclosed by Assarsson et al. in U.S. Patent No. 3,901,236 issued August 26, 1975, which is hereby incorporated herein by reference. Processes for preparing synthetic absorbent gelling polymers are disclosed in U.S. Patent No. 4,076,663 issued February 28, 1978 to Masuda et al. and U.S. Patent No. 4,286,082 issued

August 25, 1981 to Tsubakimoto et al., both of which are hereby incorporated herein by reference.

Synthetic absorbent gelling materials typically are xerogels which form hydrogels when wetted. The term "hydrogel", however, has commonly been  
 5 used to also refer to both the wetted and unwetted forms of the material.

As mentioned previously, the high-absorbency material used in the absorbent is generally in the form of discrete particles. The particles can be of any desired shape, for example, spiral or semi-spiral, cubic, rod-like, polyhedral, etc. Shapes having a large greatest dimension/smallest dimension  
 10 ration, like needles, flakes and fibers, are also contemplated for use herein. Conglomerates of particles of absorbent gelling material may also be used in the absorbent. Desired for use are particles having an average size of from about 20 microns to about 1 millimeter. "Particle size" as used herein means the hydrophilic fibers and high-absorbency particles can be configured to form an  
 15 average composite basis weight which is within the range of about 50 -1500 gsm. In certain aspects of the invention, the average composite basis weight is within the range of about 200 - 1200 gsm, and alternatively is within the range of about 200 -1200 gsm, and alternatively is within the range of about 500 -800 gsm to provide desired performance. Furthermore, the proportion of high  
 20 absorbency particles can range from about 0 to about 100% and the proportion of fibrous material from about 0 to about 100%. Additionally, high absorbency fibers can be used such as Oasis Type 121 and Type 122 superabsorbent fibers available from Technical Absorbent Ltd., Grimsby, Lincolnshire, United Kingdom.

The retention portion **70** has laterally opposed side edges **74** and preferably is made of a single layer of material. The retention portion preferably has an hour-glass shape with enlarged end regions. Alternatively, the retention portion can include a folded or multi-layered configuration. The retention portion preferably has a length substantially equal to, or slightly  
 30 shorter than, the length of the absorbent composite. The retention portion can

include one or more barrier layers attached to the absorbent material. In one embodiment, an upper tissue substrate **88** is disposed adjacent the retention portion. Alternatively, a lower tissue substrate can be disposed adjacent an opposite side of the retention portion, or the tissue can completely envelope the retention position.

Referring to FIG. 1, the opposite garment side of the end regions **56**, **58** of the absorbent composite, and in particular, the outer, garment side surface of the backsheet **68**, are secured to the bodyside surface of the longitudinally opposed crotch ends of the first and second body panels **4**, **6**. It should be understood that the absorbent composite can be secured using any of the methods of attachment described above, including for example various adhesives **77**, stitching or other bonding methods. The absorbent composite can be secured to the body panels with any configuration of attachment lines, swirls, patterns, spots, etc., or can be a full and continuous attachment therebetween.

Although the present invention has been described with reference to preferred embodiments, those skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention. As such, it is intended that the foregoing detailed description be regarded as illustrative rather than limiting and that it is the appended claims, including all equivalents thereof, which are intended to define the scope of the invention.